

# **SPECIFICATION**

## **8'6"W x 18'L Transportable Shower/Restroom**

### **Wide Body Advantage Series**

#### **CHASSIS & FRAME:**

Heavy duty 12"x 4" 16lb. structural steel wide flange main beams  
2"x 2"x 16 ga. galvanized steel tubing floor joists 16"o.c.  
Heavy duty extruded aluminum top rail  
One (1) 10,000 lb. tongue mounted frame jack  
Four (4) 7,000 lb. leveling jacks, one at each corner  
Two (2), axles with electric brakes and emergency breakaway kit  
2 5/16" ball hitch, bumper pull

#### **EXTERIOR WALLS, ROOFING & INSULATION**

2x4 wood wall studs 16"o.c.  
2x6 wood roof rafters 16"o.c.  
R-11 insulation in walls, ceiling and floor  
.040 thick smooth aluminum siding with baked on white enamel finish  
.040 thick seamless one piece aluminum roof, maintenance free, fastened to the top rail  
with all fastener penetrations located outside the unit to eliminate water leaks

#### **INTERIOR WALL, CEILING & FLOORING**

Seamless Fiberglass Reinforced Plastic (FRP) laminated to 3/8" plywood on interior walls and ceiling with corner seams vinyl trimmed and sealed with a high quality silicone sealant to provide a very durable and waterproof interior  
3/4" marine grade tongue and groove plywood sub-flooring  
Seamless, non-slip rubberized floor coved up the walls to provide a very durable waterproof floor  
Floor drains

#### **ELECTRICAL**

Fluorescent light fixtures, rated for wet locations, includes positive latches to secure the diffuser, operated by a breaker  
20 amp NEMA 3R (weathertite) panel boxes, located on the front wall  
120v/60hz/1Ø  
Four duplex receptacles, GFCI protected  
DOT approved running lights  
Two Roof mounted A/C units with 13,500 BTU's cooling and 5,600 BTU's heating  
Wall mounted exterior lights mounted in recessed reflector pan at Entry/Exit doors

#### **PLUMBING & INTERIOR FACILITIES**

A fresh water connection with pressure regulator is included  
A waste water connection with 3" slide valve and 2" fitting and cap is included

Steel waste tank, sandblasted and coated with a coal tar epoxy, mounted under trailer with cleanout and sight glass  
Low consumption flushing Thetford toilets  
Porcelain covered steel sinks with water saving faucets in locking aluminum vanity cabinet with mirror  
14"x 14" domed skylight roof vent  
Showers stalls with curtain, brass mixing valves, 2.5 GPM shower head and chain pull shower valve  
Plumbing lines are high density cross linked polyethylene tubing with brass swaged lock fittings  
Clothes hooks  
50 gallon LPG water heaters  
LPG piping is black iron pipe terminated at the trailer's edge for connection to customer furnished fuel source

### **DOORS & STEPS**

Heavy duty custom built doors with galvanized steel cores, aluminum exterior skins, FRP interior skins, sandwiched between an aluminum extruded trim channel, weather protective neoprene bulb seal, drip shield, continuous hinge with vinyl dust cover, hydraulic closer, pull handles both sides and dead bolt locks keyed alike with thumb throw interior function

Heavy duty fold-out steps with large platforms and handrails

### **NOTE:**

- 1. In a continuing effort to improve products, pricing and contents are subject to change without notice.**
- 2. Not included are trash receptacles, soap dispensers and paper towel dispensers.**
- 3. Engineered drawings and code compliance are not included in this quotation**

## **COMMERCIAL NOTES**

Prices are good for a period of 30 days.

Completion may be expected approximately 8-12 weeks after receipt of order.

A deposit of 50% is required when placing order, balance due upon completion.