SPECIFICATION 8'6''W x 24'L Transportable Shower/Restroom Wide Body Advantage Series

CHASSIS & FRAME:

Heavy duty 12"x 4" 16lb. structural steel wide flange main beams 2"x 2"x 16 ga. galvanized steel tubing floor joists 16"o.c. Heavy duty extruded aluminum top rail One (1) 10,000 lb. tongue mounted frame jack Four (4) 7,000 lb. leveling jacks, one at each corner Two (2), axles with electric brakes and emergency breakaway kit 2 5/16" ball hitch, bumper pull

EXTERIOR WALLS, ROOFING & INSULATION

2x4 wood wall studs 16"o.c.

- 2x6 wood roof rafters 16"o.c.
- R-11 insulation in walls, ceiling and floor
- .040 thick smooth aluminum siding with baked on white enamel finish
- .040 thick seamless one piece aluminum roof, maintenance free, fastened to the top rail with all fastener penetrations located outside the unit to eliminate water leaks

INTERIOR WALL, CEILING & FLOORING

Seamless Fiberglass Reinforced Plastic (FRP) laminated to 3/8" plywood on interior walls and ceiling with corner seams vinyl trimmed and sealed with a high quality silicone sealant to provide a very durable and waterproof interior

³/₄" marine grade tongue and groove plywood sub-flooring

Seamless, non-slip rubberized floor coved up the walls to provide a very durable waterproof floor

Floor drains

ELECTRICAL

Six Four foot, 2 tube fluorescent light fixtures, rated for wet locations, includes positive latches to secure the diffuser, operated by a breaker

Two Roof mounted A/C unit with 13,500 BTU's cooling and 5.600 BTU's heating, Two 20 amp, NEMA 3R (weathertite) panel boxes, located on the front wall

120v/60hz/1ø

Two duplex receptacles, GFCI protected, one per side

DOT approved running lights

Wall mounted exterior lights at Entry/Exit doors

PLUMBING & INTERIOR FACILITIES

A fresh water connection with pressure regulator is included

A waste water connection with 3" slide valve and 2" camlock fitting with cap is included Steel waste tank, sandblasted and coated with a coal tar epoxy, mounted under

trailer with cleanout and sight glass

- Low consumption flushing Thetford toilets with stainless steel partitions and doors, with transportation locks, and heavy duty extruded aluminum clamp on, bolt thru partition hardware
- Stainless steel sinks with water saving faucets in locking aluminum vanity cabinet with mirror
- 14"x 14" domed skylight roof vents
- Aluminum showers stalls with curtain, brass mixing valves, shower head and chain pull shower valve
- Dressing area with locking door and aluminum fold down bench.
- Plumbing lines are high density cross linked polyethylene tubing with brass swaged lock fittings
- Two 50 gallon LPG Water heaters installed in utility compartment
- Four 60lb LPG cylinders with manual changeover regulators, mounted in a heavy duty steel storage rack on the rear platform

DOORS & STEPS

Heavy duty custom built doors with galvanized steel cores, aluminum exterior skins, FRP interior skins, sandwiched between an aluminum extruded trim channel, weather protective neoprene bulb seal, drip shield, continuous hinge with vinyl dust cover, hydraulic closer, pull handles and dead bolt locks keyed alike

Heavy duty fold-out steps with large platforms and handrails with aluminum privacy screens on front and rear Entry/Exit doors

NOTE:

- **1.** In a continuing effort to improve products, pricing and contents are subject to change without notice.
- 2. Not included are trash receptacles, soap dispensers and paper towel dispensers.
- 3. Engineered drawings and code compliance are not included in this quotation