



8720 Lambright Road | Houston, TX 77075  
(713) 609-1287 | info@acsi-us.com

## HEAT WAVE III

### OUR COMPACT PORTABLE FULL-FLOW DIESEL FIRED WATER HEATER

#### FEATURES & BENEFITS:

- Rugged square steel tubing frame and two solid rubber wheels make the unit easy to load, unload and transport
- High-efficiency heat exchanger supports flow rates of an average 7 gallons per minute (with no water mixing) with a 50° temperature rise
- Digital temperature controller with LED readout and passcode protected settings precisely modulates outlet temperature to 92°
- Safety features including redundant water flow switch, temperature safety valves, and a GFCI supply cord
- Five-gallon heavy-duty removable steel fuel tank and quick coupled fuel supply lines for easy refueling
- Optional hydraulic-powered chemical injection pump allows for precisely metered solution injection into the outlet stream



#### DIMENSIONS

35" L x 24" W 46" H

#### WEIGHT

205 lbs

#### POWER REQUIREMENTS

115 VAC, 60 Hz, 5.5 Amp

#### CAPACITY

Minimum Input Flow: 12 gallons per minute  
Maximum Flow Rate: 10 gallons per minute  
Input Pressure: 40 - 120 psi  
Thermal Capacity: 248,000 BTUH per hour

#### FUEL

Fuel Type: Diesel  
Fuel Tank Capacity: 5 Gallons  
Maximum Fuel Consumption: 1.77 gallons per hour