



8720 Lambright Road | Houston, TX 77075
(713) 609-1287 | info@acsi-us.com

VERSI HEAT II

OUR PORTABLE BLENDING DIESEL FIRED WATER HEATER

FEATURES & BENEFITS:

- Rugged square steel tubing frame and two solid rubber wheels make the unit easy to load, unload and transport
- High-efficiency heat exchanger supports flow rates of an average 14 gallons per minute (with no water mixing) with a 50° temperature rise
- Digital temperature controller with LED readout and passcode protected settings precisely modulates outlet temperature to 92°
- Safety features including redundant water flow switch, temperature safety valves, and a GFCI supply cord
- Five-gallon heavy-duty removable steel fuel tank and quick coupled fuel supply lines for easy refueling
- Optional hydraulic-powered chemical injection pump allows for precisely metered solution injection into the outlet stream



DIMENSIONS

35" L x 24" W x 54" H

WEIGHT

355 lbs

POWER REQUIREMENTS

115 VAC, 60 Hz, 5.5 Amp

OUTLETS

Fresh Water outlets 2 w/
valves

Solution Outlets (Optional)
2 w/valves

CAPACITY

Minimum Input Flow: 18 gallons per minute
Maximum Flow Rate: 14 gallons per minute
Input Pressure: 90 – 120 psi
Thermal Capacity: 538,000 BTUH per hour

FUEL

Fuel Type: Diesel
Fuel Tank Capacity: 5 Gallons
Maximum Fuel Consumption: 1.77 gallons per hour