



8'6"W x 32'L

Transportable Comfort Station Wide Body Advantage Series

Chassis & Frame:

- Heavy duty 12"x 4" 16lb. structural steel wide flange main beams
- 2"x 2"x 16 ga. primed steel tubing floor joists 16" o.c.
- Heavy duty extruded aluminum top rail
- One (1) 10,000 lb. tongue mounted frame jack
- Four (4) 7,000 lb. leveling jacks, one at each corner
- Three (3) 6,000 lbs axles with electric brakes and emergency breakaway kit
- 2 5/16" ball hitch, bumper pull

Exterior Walls, Roofing & Insulation:

- 2x4 wood wall studs 16" o.c.
- 2x6 wood roof rafters 16" o.c.
- R-11 insulation in walls, ceiling, and floor
- .040 thick smooth aluminum siding with baked on white enamel finish (fastenerless)
- .040 thick seamless one piece aluminum roof, maintenance free, fastened to the top rail with all fastener penetrations located outside the unit to eliminate water leaks

Interior Wall, Ceiling & Flooring:

- Seamless fiberglass Reinforced Plastic (FRP), white, laminated to 3/8" plywood on interior walls and ceiling with corner seams vinyl trimmed and sealed with a high quality silicone sealant to provide a very durable and waterproof interior
- 3/4" Advantech subflooring
- TPO rubberized raised coin floor, grey, with grey rubber cove base

Electrical:

- Interior lights to include LED recessed can lights, 120v, operated by a breaker
- Two (2) roof mounted A/C units with 13,500 BTU's cooling and 5,600 BTU's heating, one located on each side
- 20 amp, NEMA 3R (weatherize) panel box(es), located on the rear wall 120v/60hz/1Ø
- DOT approved running lights
- Wall mounted led exterior lights located at each main door

Plumbing & Interior Facilities:

- A Fresh water hookup with pressure regulator is included ¾" garden hose connection
- A waste hookup with 3" slide valve with 2" fitting and cap is included, located on street side near front
- Steel waste tank, coated with an epoxy liner, mounted under trailer with cleanout and sight glass. Tank is sloped to the street side and the capacity is approximately 1,300 gallons
- Ten (10) low consumption flushing Sealand #310 toilets with poly partitions and doors, with transportation locks, and heavy duty extruded aluminum clamp on, bolt thru partition hardware
- Grey poly, 1" thick, partitions, urinal blinds, and countertops
- Six (6) porcelain covered steel sinks with push button water saving faucets mounted on a poly countertop with 48" and 24" locking aluminum vanity cabinets (white) and mirror.
- Four (4) wall hung porcelain urinals with integral P-trap and with metered flush valves
- 14"x 14" domed skylight roof vents with aerodynamic covers

Doors & Steps:

- Two (2) heavy duty custom built ACSI SIP doors with weather protective neoprene bulb seal, drip shield, continuous hinge with vinyl dust cover, hydraulic closer, pull handle and dead bolt locks keyed alike
- Heavy duty steel fold-out steps with large drop in step landing, fully supported by chassis
- Aluminum folding handrails (3 point connection) located at entry/exit doors

Note:

1. In a continuing effort to improve products, pricing and contents are subject to change without notice.
2. Not included are trash receptacles, soap dispensers and paper towel dispensers
3. Engineered drawings and code compliance are not included in this quotation.